

Materials Safety Data Sheet (MSDS) FastCoat Pro 2-Part Humidity Primer Comp B

Section 1: Identification of the Mixture and of the Company / Undertaking.

1.1 Product identifier.

Product Name: Humidity Primer Comp.B

Product Code: P20

1.2 Relevant identified uses of the mixture and uses advised against.

Coating

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: Liquid Roofing Systems Ltd

Address: Prees Green

City: Shropshire

Telephone: 01948 841 877

Fax: 01948 841 854

Web: Irs-systems.co.uk

1.4 Emergency telephone number: 01948 841 877 (Only available during office hours)

Section 2: Hazards Identification.

2.1 Classification of the mixture.

In accordance with Regulation (EU) No 1272/2008:

Eye Dam. 1: Causes serious eye damage.

Skin Irrit. 2: Causes skin irritation.

Skin Sens. 1: May cause an allergic skin reaction.



2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:



Signal Word:

Danger

H statements:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

P statements:

P280 Wear protective gloves/protective clothing/eye protection/face protection. P310 Immediately call a POISON CENTER/doctor/...

P501 Dispose of contents/container to ... P302+P352 IF ON SKIN: Wash with plenty of water/...

P332+P313 If skin irritation occurs: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Contains:

Functional copolymer made of Bisphenol A/F, epichlorhydrine, polyethyleneglycol, triethylenetetramine, cresyl glycidyl ether, alkyl glycidyl ether, phenyl glycidyl ether and diethylenetriamine

2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.



<u>Section 3 Composition / Information on Ingredients.</u>

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	specific concentration limit
Index No: n.d. CAS No: 1312024-58- 0 EC No: n.d.	Functional copolymer made of Bisphenol A/F, epichlorhydrine, polyethyleneglycol, triethylenetetramine, cresyl glycidyl ether, alkyl glycidyl ether, phenyl glycidyl ether and diethylenetriamine	10 - 50 %	Eye Dam. 1, H318 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	-

^(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

Section 4: First Aid Measures.

IRRITANT PREPARATION. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.

If wearing contact lenses, remove them. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.



Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate. Can cause allergic reactions.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Section 5: Firefighting Measures.

5.1 Extinguishing media. Recommended extinguishing methods.

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray. Do not use a direct stream of water to extinguish.

5.2 Special hazards arising from the mixture. Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and gloves.



Section 6: Accidental Release Measures.

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Pick up the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomite, etc.). Pour the product and the absorbent in an appropriate container. The contaminated area should be immediately cleaned with an appropriate de- contaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

Section 7: Handling and Storage.

7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti- static footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8. Never use pressure to empty the containers. They are not pressure-resistant containers.

In the application area, smoking, eating, and drinking must be prohibited. Follow legislation on occupational health and safety.

Keep the product in containers made of a material identical to the original.



7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 35° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

Section 8: Exposure Controls / Personal Protection.

8.1 Control parameters.

The product does NOT contain substances with Professional Exposure Environmental Limit Values. The product does NOT contain substances with Biological Limit Values.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %		
Uses:	Coating		
Breathing protection:			
PPE:	Filter mask for protection against gases and particles.		
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.		
CEN standards:	EN 136, EN 140, EN 405		
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.		
Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.		
Filter Type needed:	A2 , , , , , , , , , , , , , , , , , , ,		
Hand protection:			
PPE: Characteristics:	Protective gloves against chemicals. «CE» marking, category III.		
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420		
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.		
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.		
	PVC (polyvinyl chloride) Breakthrough time (min.): Material thickness (mm): 0,35		
Eye protection:			
PPE: Characteristics:	Face shield.		



«CE» marking, category II. Face and eye protector against splashing liquid. CEN standards: EN 165, EN 166, EN 167, EN 168 Maintenance: Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move Observations: smoothly. Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame. Skin protection: PPE: Anti-static protective clothing. «CE» marking, category II. Protective clothing should not be too tight or loose in Characteristics: order not to obstruct the user's movements. CEN standards: EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5 In order to guarantee uniform protection, follow the washing and maintenance instructions provided by Maintenance: the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided in Observations: terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use. PPE: Anti-static safety footwear. Characteristics: «CE» marking, category II. CEN standards: EN ISO 13287, EN ISO 20344, EN ISO 20346 Maintenance: The footwear should be checked regularly The level of comfort during use and acceptability are factors that are assessed very differently depending on the Observations: user. Therefore, it is advisable to try on different footwear models and, if possible, different widths.

Section 9: Physical and Chemical Properties.

9.1 Information on basic physical and chemical properties.

Appearance: Liquid with characteristic odour and colour: light brown

Odour: amines

Odour threshold: N.A./N.A. pH:>7

Melting point: n.d. °C Boiling Point: -- °C Flash point: -- °C Evaporation rate: n.d.

In flammability (solid, gas): non-flammable Lower Explosive Limit: n.d.

Upper Explosive Limit: N.A./N.A. Vapour pressure: n.d.

Vapour density: n.d.

Relative density: 1.05 g/cm3 g/cm3 Solubility: water

Lip solubility: not determined Hydro solubility: soluble

Partition coefficient (n-octanol/water): not determined Auto-ignition temperature: N.A./N.A.

Decomposition temperature: N.A./N.A. Viscosity: <1000 cP at 25°C

Explosive properties: n.d. Oxidizing properties: n.d.

Materials Safety Data Sheet FastCoat Pro 2-Part Humidity Primer Jan 2019, Version 10



N.A./N.A.= Not Available/Not Applicable due to the nature of the product

9.2. Other information.

Volatile organic compound (VOC)

Product Subcategory: Two-pack reactive performance coatings for specific end use such as floors, water-borne Phase I* (from 01/01/2007): 140 g/l

Phase II* (from 01/01/2010): 140 g/l (*) g/l ready to use

VOC content (p/p): 0 % VOC content: 2 g/l Pour point: n.d.

Blink: n.d.

Kinematic viscosity: n.d.

Section 10: Stability and Reactivity.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.



Section 11: Toxicological Information.

IRRITANT PREPARATION. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

11.1 Information on toxicological effects.

There are no tested data available on the product.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation; Product classified:

Skin irritant, Category 2: Causes skin irritation.

c) serious eye damage/irritation; Product classified:

Serious eye damage, Category 1: Causes serious eye damage.

d) respiratory or skin sensitisation; Product classified:

Skin sensitiser, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Not conclusive data for classification.

h) STOT-single exposure;

Not conclusive data for classification.

i) STOT-repeated exposure;

Not conclusive data for classification.

i) aspiration hazard;

Not conclusive data for classification. Materials Safety Data Sheet FastCoat Pro 2-Part Humidity Primer



Section 12: Ecological Information.

12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

12.2 Persistence and degradability.

No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potencial.

No information is available regarding the bioaccumulation of the substances present.

12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways. Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

Section 13: Disposal Considerations.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.



Section 14: Transport Information.

Transportation is not dangerous. In case of road accident causing the product's spillage, proceed in accordance with point 6.

14.1 UN number.

Transportation is not dangerous.

14.2 UN proper shipping name.

Transportation is not dangerous.

14.3 Transport hazard class(es).

Transportation is not dangerous.

14.4 Packing group.

Transportation is not dangerous.

14.5 Environmental hazards.

Transportation is not dangerous.

14.6 Special precautions for user.

Transportation is not dangerous.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code.

Transportation is not dangerous.



Section 15: Regulatory Information.

15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

See annex I of the Directive 96/82/EC of 9 December 1996 on the control of major-accident hazards involving dangerous substances.

The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

The product is not affected by Directive 2012/18/EU (SEVESO III).

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

15.2 Chemical safety assessment.

There has been no evaluation a chemical safety assessment of the product.

Section 16: Other Information.

Complete text of the H phrases that appear in section 3:

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.



Classification codes:

Eye Dam. 1: Serious eye damage, Category 1 Skin Irrit. 2: Skin irritant, Category 2

Skin Sens. 1: Skin sensitiser, Category 1

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Labelling in accordance with Directive 1999/45/EC:

Symbols:

Χi



Irritant

R Phrases:

R38 Irritating to skin.

R41 Risk of serious damage to eyes.

S Phrases:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S39 Wear eye/face protection.

S60 This material and its container must be disposed of as hazardous waste.

Abbreviations and acronyms used:

CEN: European Committee for Standardization. PPE: Personal protection equipment.

Key literature references and sources for data: http://eur-lex.europa.eu/homepage.html http://echa.europa.eu/

Regulation (EU) 2015/830.

Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.



The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

Legal Notes

The information, and in particular, the recommendations relating to the application and the end use of FastCoat Pro 2-Part Humidity Primer, are given in good faith based on LRS current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with LRS recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no guarantee in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from ant other advice offered. The user of the product must test the product's suitability for the intended application and purpose. LRS reserves the right to change the properties of its products. The proprietary rights of the third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local product data sheet for the product concerned, copies of which will be supplied on request.

