

# Safety data sheet

## according to 1907/2006/EC, Article

31

Revision: 29.09.2020



Vers.No.: 2

Printing date 30.09.2020

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: RapidRepair**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
Unsuitable for home DIY applications.
- **Application of the substance / the preparation:** Reaction resin
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
LRS  
Prees Green  
SY13 2BN  
Tel.: 01948 841 877  
e-mail: info@lrs-systems.co.uk
- **Further information obtainable from:** Environmental department
- **1.4 Emergency telephone number:** 01948 841 877

### SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**  
Flam. Liq. 2 H225 Highly flammable liquid and vapour.  
Skin Irrit. 2 H315 Causes skin irritation.  
Eye Irrit. 2 H319 Causes serious eye irritation.  
Skin Sens. 1 H317 May cause an allergic skin reaction.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**  
  
  
GHS02 GHS07
- **Signal word** Danger
- **Hazard-determining components of labelling:**  
n-butyl acrylate  
methyl methacrylate  
N,N-Bis-(hydroxyethyl)-para-toluidine
- **Hazard statements**  
H225 Highly flammable liquid and vapour.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.
- **Precautionary statements**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. **No** smoking.  
**P261** Avoid breathing **dust/fume/gas/mist/vapours/spray**.  
P280 Wear **protective gloves/protective clothing/eye protection/face protection**.  
P370+P378 **In case of fire: Use fire extinguishers: CO2, powder or water spray.**  
P403+P235 Store in a well-ventilated place. Keep cool.

(Contd. on page 2)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 30.09.2020

Vers.No.: 2

Revision: 29.09.2020

Trade name: RapidRepair

(Contd. of page 1)

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

#### · Dangerous components:

CAS: 7727-43-7 EINECS: 231-784-4	barium sulphate, natural substance with a Community workplace exposure limit	25-50%
CAS: 141-32-2 EINECS: 205-480-7 Reg.nr.: 01-2119453155-43-xxxx	n-butyl acrylate ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	10-25%
CAS: 80-62-6 EINECS: 201-297-1 Reg.nr.: 01-2119452498-28	methyl methacrylate ⚠ Flam. Liq. 2, H225; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	10-25%
CAS: 103671-44-9 Reg.nr.: 01-2119979579-10-xxxx	N,N-Bis-(hydroxyethyl)-para-toluidine ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412	0.5-2.5%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** If symptoms persist consult doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
Foam  
Sand  
CO<sub>2</sub>, powder or water spray. Fight larger fire with alcohol resistant foam.  
CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:**  
Water  
Water with full jet
- **5.2 Special hazards arising from the substance or mixture**  
Exothermic polymerisation.  
**In case of fire, the following can be released:**  
**Hydrocarbons**

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 30.09.2020

Vers.No.: 2

Revision: 29.09.2020

**Trade name: RapidRepair**

(Contd. of page 2)

- Carbon monoxide and carbon dioxide
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.
- **Additional information** Cool endangered receptacles with water spray.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

- Ensure adequate ventilation
- Wear protective clothing.
- Keep away from ignition sources.
- Use respiratory protective device against the effects of fumes/dust/aerosol.
- Wear protective equipment. Keep unprotected persons away.

#### · 6.2 Environmental precautions:

- Do not allow product to reach sewage system or any water course.
- Prevent seepage into sewage system, workpits and cellars.
- Inform respective authorities in case of seepage into water course or sewage system.
- Do not allow to enter sewers/ surface or ground water.

#### · 6.3 Methods and material for containment and cleaning up:

- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).
- Ensure adequate ventilation.
- Do not flush with water or aqueous cleansing agents

#### · 6.4 Reference to other sections

- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

### SECTION 7: Handling and storage

#### · 7.1 Precautions for safe handling

- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.

#### · Information about fire - and explosion protection:

- Fumes can combine with air to form an explosive mixture.
- Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.

#### · 7.2 Conditions for safe storage, including any incompatibilities

##### · Storage:

##### · Requirements to be met by storerooms and receptacles:

- Store only in the original receptacle.
- Store in cool, dry conditions in well sealed receptacles.
- Do not allow to enter sewers/ surface or ground water.
- Store in a cool location.

##### · Information about storage in one common storage facility: Not required.

##### · Further information about storage conditions:

- Store receptacle in a well ventilated area.
- Keep container tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.

##### · Maximum storage temperature: 25°C

##### · 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 30.09.2020

Vers.No.: 2

Revision: 29.09.2020

Trade name: RapidRepair

(Contd. of page 3)

### · 8.1 Control parameters

#### · Ingredients with limit values that require monitoring at the workplace:

<b>7727-43-7 barium sulphate, natural</b>	
WEL	Long-term value: 10* 4** mg/m <sup>3</sup> *inhalable dust **respirable dust
<b>141-32-2 n-butyl acrylate</b>	
WEL	Short-term value: 26 mg/m <sup>3</sup> , 5 ppm Long-term value: 5 mg/m <sup>3</sup> , 1 ppm
<b>80-62-6 methyl methacrylate</b>	
WEL	Short-term value: 416 mg/m <sup>3</sup> , 100 ppm Long-term value: 208 mg/m <sup>3</sup> , 50 ppm

· **Additional information: The lists valid during the making were used as basis.**

### · 8.2 Exposure controls

#### · Personal protective equipment:

#### · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

#### · Respiratory protection:

Use the indicated respiratory protection if workplace exposure limits are exceeded.

#### · Recommended filter device for short term use: Filter A

#### · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation (EN 374)

#### · Material of gloves Butyl rubber, BR

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### · Eye protection:



Tightly sealed goggles

#### · Body protection: Protective work clothing

## SECTION 9: Physical and chemical properties

### · 9.1 Information on basic physical and chemical properties

#### · General Information

#### · Appearance:

Form:

Fluid

Colour:

According to product specification

#### · Odour:

Characteristic

#### · Odour threshold:

Not determined.

(Contd. on page 4)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 30.09.2020

Vers.No.: 2

Revision: 29.09.2020

Trade name: RapidRepair

(Contd. of page 4)

· pH-value:	Not determined.
· <b>Change in condition</b>	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	100 °C
· Flash point:	10 °C
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	275 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <b>Explosion limits:</b>	
Lower:	1.2 Vol %
Upper:	12.5 Vol %
· Vapour pressure at 20 °C:	38.7 hPa
· Density at 20 °C:	1.4 g/cm <sup>3</sup>
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic at 20 °C:	16,000 mPas
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	0.0 %
Solids content:	50.0 %
· 9.2 Other information	No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** Keep away from heat and direct sunlight.
- **10.3 Possibility of hazardous reactions** Exothermic polymerisation.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** Reacts with peroxides and other radical forming substances.
- **10.6 Hazardous decomposition products:**  
Hydrocarbons  
Carbon monoxide and carbon dioxide
- **Additional information:**  
Do not allow product to reach sewage system or any water course.  
Prevent seepage into sewage system, workpits and cellars.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.

GB

(Contd. on page 5)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 30.09.2020

Vers.No.: 2

Revision: 29.09.2020

Trade name: RapidRepair

(Contd. of page 5)

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation**  
May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must be specially treated adhering to official regulations.  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

#### · European waste catalogue

07 02 08*	other still bottoms and reaction residues
15 01 10*	packaging containing residues of or contaminated by hazardous substances

- **Uncleaned packaging:**
- **Recommendation:**  
Packaging may be reused or recycled after cleaning.  
Packagings that may not be cleansed are to be disposed of in the same manner as the product.
- **Recommended cleansing agents:** Acetone, ethylacetate

(Contd. on page 7)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 30.09.2020


Vers.No.: 2

Revision: 29.09.2020

Trade name: RapidRepair

(Contd. of page 6)

### SECTION 14: Transport information

<ul style="list-style-type: none"> <li>· 14.1 UN-Number</li> <li>· ADR, IMDG, IATA</li> </ul>	UN1866
<ul style="list-style-type: none"> <li>· 14.2 UN proper shipping name</li> <li>· ADR</li> <li>· IMDG, IATA</li> </ul>	1866 RESIN SOLUTION RESIN SOLUTION
<ul style="list-style-type: none"> <li>· 14.3 Transport hazard class(es)</li> <li>· ADR, IMDG, IATA</li> </ul>	
	
<ul style="list-style-type: none"> <li>· Class</li> <li>· Label</li> </ul>	3 Flammable liquids. 3
<ul style="list-style-type: none"> <li>· 14.4 Packing group</li> <li>· ADR, IMDG, IATA</li> </ul>	III
<ul style="list-style-type: none"> <li>· 14.5 Environmental hazards:</li> <li>· Marine pollutant:</li> </ul>	No
<ul style="list-style-type: none"> <li>· 14.6 Special precautions for user</li> <li>· Hazard identification number (Kemler code):</li> <li>· EMS Number:</li> <li>· Stowage Category</li> </ul>	Warning: Flammable liquids. 33 F-E, <u>S</u> -E A
<ul style="list-style-type: none"> <li>· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</li> </ul>	Not applicable.
<ul style="list-style-type: none"> <li>· Transport/Additional information:</li> </ul>	
<ul style="list-style-type: none"> <li>· ADR</li> <li>· Limited quantities (LQ)</li> <li>· Excepted quantities (EQ)</li> </ul>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<ul style="list-style-type: none"> <li>· Transport category</li> <li>· Tunnel restriction code</li> </ul>	3 E
<ul style="list-style-type: none"> <li>· IMDG</li> <li>· Limited quantities (LQ)</li> <li>· Excepted quantities (EQ)</li> </ul>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<ul style="list-style-type: none"> <li>· UN "Model Regulation":</li> </ul>	UN 1866 RESIN SOLUTION, 3, III

### SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

(Contd. on page 8)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 30.09.2020

Vers.No.: 2

Revision: 29.09.2020

**Trade name: RapidRepair**

(Contd. of page 7)

- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

<ul style="list-style-type: none"> <li>· <b>DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II</b></li> </ul>
---

None of the ingredients is listed.
------------------------------------

- **National regulations:**
- **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H225 Highly flammable liquid and vapour.  
 H226 Flammable liquid and vapour.  
 H302 Harmful if swallowed.  
 H312 Harmful in contact with skin.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H332 Harmful if inhaled.  
 H335 May cause respiratory irritation.  
 H412 Harmful to aquatic life with long lasting effects.

- **Department issuing SDS:** Environmental Department

- **Abbreviations and acronyms:**

Flam. Liq. 2: Flammable liquids – Category 2  
 Flam. Liq. 3: Flammable liquids – Category 3  
 Acute Tox. 4: Acute toxicity - dermal – Category 4  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
 Skin Sens. 1: Skin sensitisation – Category 1  
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

- **\* Data compared to the previous version altered.**

GB