Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.11.2020

Vers.No.: 4

Revision: 25.11.2020

SECTION 1: Identification of the substance/mixture and of the company/ undertaking 1.1 Product identifier

Trade name: RapidRoof Primer

1.2 Relevant identified uses of the substance or mixture and uses advised against Unsuitable for home DIY applications.

- · Application of the substance / the preparation: Reaction resin
- 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier:
- LRS, Prees Green, Shropshire, SY13 4QL Tel.: +01948 841877

e-mail: info@lrs-systems.co.uk

· Further information obtainable from: Environmental department 1.4 Emergency telephone number: 01948 841877

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Lig. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eve Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

· 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation. Hazard pictograms



· Signal word Danger

· Hazard-determining components of labelling: n-butyl acrylate methyl methacrylate Triethylene glycol dimethacrylate N-Hydroxyethyl-N-methyl-p-toluidine **Hazard statements** H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

(Contd. on page 2)





Printing date 25.11.2020

Vers.No.: 4

Revision: 25.11.2020

(Contd. of page 1) Precautionary statements Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No P210 smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. P261 P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P370+P378 In case of fire: Use for extinction: CO2, powder or water spray. P403+P233 Store in a well-ventilated place. Keep container tightly closed. Dispose of contents/container in accordance with local/regional/national/international P501 regulations. 2.3 Other hazards Results of PBT and vPvB assessment • PBT: Not applicable. vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 141-32-2 EINECS: 205-480-7 Reg.nr.: 01-2119453155-43- xxxx	n-butyl acrylate Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	25-50%	
CAS: 80-62-6 EINECS: 201-297-1 Reg.nr.: 01-2119452498-28	methyl methacrylate Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	10-25%	
CAS: 109-16-0 EINECS: 203-652-6 Reg.nr.: 01-2119969287-21	Triethylene glycol dimethacrylate Skin Sens. 1B, H317	0.5-2.5%	
CAS: 2842-44-6 EINECS: 220-638-5 Reg.nr.: 01-2120827830-56	N-Hydroxyethyl-N-methyl-p-toluidine Aquatic Chronic 2, H411; () Eye Irrit. 2, H319; Skin Sens. 1, H317	0.5-2.5%	

SECTION 4: First aid measures

4.1 Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air and to be sure call for a doctor.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:
- Foam
- Sand

(Contd. on page 3)

G



Printing date 25.11.2020

Vers.No.: 4

Revision: 25.11.2020

(Contd. of CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. • For safety reasons unsuitable extinguishing agents: Water with full jet • 5.2 Special hazards arising from the substance or mixture Exothermic polymerisation. In case of fire, the following can be released: Hydrocarbons Carbon monoxide and carbon dioxide Nitrogen oxides (NOx) • 5.3 Advice for firefighters • Protective equipment: Wear self-contained respiratory protective device. • Additional information Cool endangered receptacles with water spray.	page 2)
SECTION 6: Accidental release measures	
 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation Wear protective clothing. Keep away from ignition sources. Use respiratory protective device against the effects of fumes/dust/aerosol. 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water. 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders). Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.	
SECTION 7: Handling and storage	
 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Fumes can combine with air to form an explosive mixture. 	
7.2 Conditions for safe storage, including any incompatibilities Storage:	

- Requirements to be met by storerooms and receptacles:
 Store only in the original receptacle.
 Store in cool, dry conditions in well sealed receptacles.
 Do not allow to enter sewers/ surface or ground water.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Store receptacle in a well ventilated area.
- Protect from heat and direct sunlight.
- Maximum storage temperature: 25°C
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)



Printing date 25.11.2020

Vers.No.: 4

Revision: 25.11.2020

 Inared 	ients with limit values that r	(Contd. of page contering at the workplace:
-	2-2 n-butyl acrylate	
	Short-term value: 26 mg/m ³ , 5	ppm
	Long-term value: 5 mg/m³, 1 p	
80-62-	6 methyl methacrylate	
	Short-term value: 416 mg/m³,	
ļ	Long-term value: 208 mg/m³, 5	50 ppm
· Additi	onal information: The lists va	lid during the making were used as basis.
• Person Generative Keep a Immed Wash I Avoid o Respin Use the Recon	posure controls nal protective equipment: al protective and hygienic m away from foodstuffs, beverage liately remove all soiled and co hands before breaks and at the contact with the eyes and skin. ratory protection: e indicated respiratory protection mended filter device for sho stion of hands:	es and feed. ntaminated clothing e end of work. on if workplace exposure limits are exceeded.
	Protective gloves	
prepar Selecti degrad Materi Penetr The ex has to For the accord	ation. on of the glove material on co lation (EN 374) al of gloves Butyl rubber, BR ration time of glove material act break through time has to be observed.	meable and resistant to the product/ the substance/ the onsideration of the penetration times, rates of diffusion and be found out by the manufacturer of the protective gloves a e penetration time has to be at least 60 minutes (Permeat
	Tightly sealed goggles	
Body	protection: Protective work clo	othing
9.1 Inf	TION 9: Physical and ch ormation on basic physical a al Information	• •
· Appea		
Forn		Fluid
Colo	our:	Whitish
· Odour	=	Characteristic
· Odour	threshold:	Not determined.
pH-va	ue:	Not determined.
Ohana	e in condition	
Chanc	,	
	ing point/freezing point:	Undetermined.



Printing date 25.11.2020

Vers.No.: 4

Revision: 25.11.2020

	(Contd. of page 4	
Initial boiling point and boiling range: 100 °C		
· Flash point:	10 °C	
 Flammability (solid, gas): 	Not applicable.	
· Ignition temperature:	245 °C	
· Decomposition temperature:	Not determined.	
· Auto-ignition temperature:	Product is not selfigniting.	
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.	
[·] Explosion limits: Lower: Upper:	1.2 Vol % 12.5 Vol %	
 Vapour pressure at 20 °C: 	38.7 hPa	
 Density at 20 °C: Relative density Vapour density Evaporation rate 	0.99 g/cm³ Not determined. Not determined. Not determined.	
 Solubility in / Miscibility with water: 	Not miscible or difficult to mix.	
· Partition coefficient: n-octanol/water:	Not determined.	
 Viscosity: Dynamic at 20 °C: Kinematic: 	800 mPas Not determined.	
 Solvent content: Organic solvents: 	0.0 %	
• 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

Keep away from heat and direct sunlight.

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions Exothermic polymerisation.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: Reacts with peroxides and other radical forming substances.
- 10.6 Hazardous decomposition products:

Hydrocarbons

Carbon monoxide and carbon dioxide

· Additional information: Do not allow to enter sewers/ surface or ground water.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

(Contd. on page 6)

. ЭВ-



Printing date 25.11.2020

Vers.No.: 4

Revision: 25.11.2020

(Contd. of page 5)

- Serious eye damage/irritation
- Causes serious eye irritation.
- Respiratory or skin sensitisation
- May cause an allergic skin reaction.
- Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause respiratory irritation.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- Additional ecological information:
- General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Must be specially treated adhering to official regulations.

· European waste catalogue

07 02 08 [*] other still bottoms and reaction residues

15 01 10^{*} packaging containing residues of or contaminated by hazardous substances

Uncleaned packaging:

Recommendation:

Packaging may be reused or recycled after cleaning.

Packagings that may not be cleansed are to be disposed of in the same manner as the product. Disposal must be made according to official regulations.

· Recommended cleansing agents: Acetone, ethylacetate

SECTION 14: Transport information

14.1 UN-Number
 ADR, IMDG, IATA

UN1866

(Contd. on page 7)



Printing date 25.11.2020

Vers.No.: 4

Revision: 25.11.2020

	(Contd. of page
 14.2 UN proper shipping name ADR IMDG, IATA 	1866 RESIN SOLUTION RESIN SOLUTION
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
[·] 14.4 Packing group [·] ADR, IMDG, IATA	П
[·] 14.5 Environmental hazards: [·] Marine pollutant:	No
 14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category 	Warning: Flammable liquids. 33 F-E, <u>S-E</u> B
 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code 	Not applicable.
· Transport/Additional information:	
 ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category 	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 m 2
· Tunnel restriction code	D/E
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 m
UN "Model Regulation":	UN 1866 RESIN SOLUTION, 3, II

SECTION 15: Regulatory information

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

• Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

• REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

(Contd. on page 8)



Printing date 25.11.2020

Vers.No.: 4

Revision: 25.11.2020

(Contd. of page 7)

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

National regulations:

Technical instructions (air):

Class	Share in %
	≤ 2,5
NK	10-25

• Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

- H226 Flammable liquid and vapour.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H411 Toxic to aquatic life with long lasting effects.
- · Department issuing SDS: Environmental Department

• Abbreviations and acronyms: Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity - dermal – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1B: Skin sensitisation – Category 1B STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 * **Data compared to the previous version altered.**